



- MAX 98.8% EFFICIENCY
- IP65 PROTECTION

STT 50~60kW

Three Phase | 6 MPPTs | ON Grid

- High reliability due to good heat dissipation design
- Integrated lightning protection for both DC and AC
- Adapt to complex power grid
- High anti-corrosion ability with aluminum alloy enclosure
- Wider working temperature and altitude, adapt to various installation environments

SAFE & RELIABLE



- High yield with Max. 98.8% efficiency
- European weighted efficiency 98.3%
- Up to 10% continuous output overloading capacity
- Six MPPT design, lower PV string mismatch loss
- DC 2 in 1 connection enabled, compatible with high-power panels

HIGH YIELD



- String monitoring, improve O&M efficiency
- Support wireless and wired internet connection (RS485, WiFi/GPRS/LAN optional)
- Remote upgrading available

EASY TO USE



Model	STT-50KTL-P	STT-60KTL-P
Input		
Max. Input Power (W)	80,000	96,000
Start-up Voltage (V)	200	200
Max. DC Input Voltage (V)	1,100	1,100
Rated DC Input Voltage (V)	620	620
MPPT Voltage Range (V)	160-1000	160-1000
Number of MPP Trackers	6	6
Number of DC Inputs per MPPT	2	2
Max. Input Current (A)	26/26/26/26/26/26 ^①	26/26/26/26/26/26 ^①
Max. Short-circuit Current (A)	40/40/40/40/40/40	40/40/40/40/40/40
Output		
Rated Output Power (W)**	50,000	60,000
Max. Output Power (W)	55,000	66,000
Max. Apparent Power (VA)	55,000	66,000
Rated Output Voltage (V)**	3L/N/PE, 230/400V	
Rated AC Frequency (Hz)	50/60Hz 45-55Hz/55-65Hz	
Max. Output Current (A)	83.6	95.3
Power Factor	0.8 leading...0.8 lagging	
Max. Total Harmonic Distortion	<3% @Rated Output Power	
DCI	< 0.5% In	
Efficiency		
Max. Efficiency	98.8%	98.8%
European Efficiency	98.3%	98.3%
MPPT Efficiency	99.9%	99.9%
Protection		
DC Reverse Polarity Protection	Integrated	
Insulation Resistance Protection	Integrated	
DC Switch	Optional	
Surge Protection	Integrated	
Over-temperature Protection	Integrated	
Residual Current Protection	Integrated	
Anti-islanding protection	Frequency shift, Integrated	
AC Short-circuit Protection	Integrated	
AC Over-voltage Protection	Integrated	
General Data		
Dimensions (mm)	850W*520H*290D	
Weight (kg)	58	
Protection Degree	IP65	
Self-consumption at Night (W)	< 1	
Topology	Transformerless	
Operating Temperature Range (°C)	-30~60	
Relative Humidity (%)	0~100	
Operating Altitude (m)	4000 (derating@ > 3000)	
Cooling	Smart Fan Cooling	
Noise Level (dB)	< 55	
Display	OLED & LED	
Communication	RS485, WiFi/GPRS/LAN (Optional)	
Compliance	CEI-021, EN50549, IEC61727, IEC62116, IEC60068, IEC61683, VDE0126, PTPIREE, EN61000, IEC62109	

① STT-50/60KTL series maximum input current per MPPT is 22A, products deliver upon the order.

** Due to differences in voltage values in various countries, minor variations may occur. The final interpretation rights belong to Sunways.