




- MAX. EFFICIENCY 98.1%
- IP65 PROTECTION

STS 7~11kW

Single Phase | 2 MPPTs | On Grid

- High reliability due to good heat dissipation design
- Integrated lightning protection for both DC and AC
- Adapt to complex grid environments
- High anti-corrosion ability with aluminum alloy die casting technology
- Wider working temperature and altitude, adapt to various installation environments

SAFE & RELIABLE



- High yield with Max. Efficiency 98.1%
- European weighted efficiency 97.6%
- Wide MPPT voltage range
- Up to 10% continuous output overloading capacity
- With a max input current of 15A, compatible with high-power panels

HIGH YIELD



- Plug and play connectors, easy for installation
- Support wireless and wired internet connection (RS485/WiFi/GPRS/LAN optional)
- Remote upgrading available
- Fast and easy configuration via App or OLED display

EASY TO USE



Model	STS-7KTL	STS-8KTL	STS-9KTL	STS-10KTL	STS-11KTL*
Input					
Max. Input Power (W)	11,200	12,800	14,400	16,000	16,000
Start-up Voltage (V)	80	80	80	80	80
Max. DC Input Voltage (V)	600	600	600	600	600
Rated DC Input Voltage (V)	360	360	360	360	360
MPPT Voltage Range (V)	80~550	80~550	80~550	80~550	80~550
Number of MPP Trackers	2	2	2	2	2
Number of DC Inputs per MPPT	1/2	1/2	1/2	1/2	1/2
Max. Input Current (A)	15/30	15/30	15/30	15/30	15/30
Max. Short-circuit Current (A)	20/40	20/40	20/40	20/40	20/40
Output					
Rated Output Power (W)**	7,000	8,000	9,000	10,000	11,000
Max. Output Power (W)	7,700	8,800	9,900	11,000	11,000
AC Output Rated Apparent Power (VA)	7,000	8,000	9,000	10,000	11,000
Max. Apparent Power (VA)	7,700	8,800	9,900	11,000	11,000
Grid Type (V)**	220/230				
Rated AC Frequency (Hz)	50/60				
AC Output Rated Current (A)	30.4	34.8	39.1	43.5	47.8
Max. Output Current (A)	33.5	38.3	43	47.8	47.8
Power Factor	0.8 leading...0.8 lagging				
THDi @ Rated Power	<3%				
DCI	< 0.5%In				
Efficiency					
Max. Efficiency	98.1%	98.1%	98.1%	98.1%	98.1%
Euro Efficiency	97.6%	97.6%	97.6%	97.6%	97.6%
MPPT Efficiency	99.9%	99.9%	99.9%	99.9%	99.9%
Protection					
DC Reverse Polarity Protection	Integrated				
Insulation Resistance Detection	Integrated				
DC Switch	Optional				
AFCI	Optional				
Surge Protection	Integrated				
Over-temperature Protection	Integrated				
Residual Current Protection	Integrated				
Anti-islanding Protection	Integrated				
AC Short-circuit Protection	Integrated				
AC Over-voltage Protection	Integrated				
General Data					
Dimensions [W*H*D] (mm)	550*410*175				
Weight (kg)	24	26			
Protection Degree	IP65				
Self-consumption at Night (W)	< 1				
Topology	Transformerless				
Operating Temperature Range (°C)	-30~60				
Relative Humidity (%)	0~100				
Operating Altitude (m)	4000 (derating > 3000)				
Cooling	Natural Convection		Smart Fan Cooling		
Noise Level (dB)	< 25		< 40		
Display	OLED & LED				
Communication	RS485/WiFi/GPRS/LAN (Optional)				

* STS 11KTL is only available for Brazil.

** Due to differences in voltage values in various countries, minor variations may occur. The final interpretation rights belong to Sunways.